

TRACTOR SPECIFICATIONS

Model	B1220		B1620		B1820PS	
	w/o Mid-PTO		w/ Mid PTO		w/ Mid PTO	
Engine	E-TVCS, liquid cooled, 2-cylinder diesel		E-TVCS, liquid cooled, 3-cylinder diesel			
Type						
Make, Model	Kubota Z482		Kubota D722		Kubota D782	
Engine power SAE gross	kW (PS)	8.8 (12)	11.8 (16)		13.2 (18)	
Engine power ECE-R24	kW (PS)	7.9 (11)	10.3 (14)		11.9 (16)	
PTO power ^(*)	kW (PS)	7.0 (9.5)	9.2 (12.5)		10.7 (14.5)	
No. of cylinders	2				3	
Bore & stroke	mm	67 × 68				67 × 73.6
Total displacement	cm ³	479	719		778	
Rated speed	rpm	3100			2800	
Muffler and exhaust pipe			Fully enclosed			
Air cleaner			Single			
Fuel tank capacity	ℓ					14
Drive train						
Driving method	4WD		2WD ⇄ 4WD			
Transmission speeds			F6/R2			
Max. travelling speed	km/h	15.1	17		18.1	
Differential lock			STD			
Brake type			Wet mulch disk			
Steering			Manual		Power steering	
PTO						
Rear PTO	Type	Transmission driven with one way clutch				
	Speed	rpm	540/1000			
Mid PTO ^(*)	Speed	rpm	N/A	2500		
Hydraulic system						
Pump capacity	ℓ/min	8.2	14.1			
Lift control type			Select			
Lift capacity	Link end	kg	430	540		
Max. operating pressure	kg/cm ²	91	123			
3-point hitch			category I			
Hydraulic outlets	1 rear (OPT)				1 rear & 1 mid	
Hydraulic cylinder for mower lifting			N/A			
Dimensions						
Overall length	mm			2360		
Overall width (min. tread)	mm	932				940
Overall height (Steering wheel / ROPS)	mm	1235 / N/A	1235 / 2230		1255 / 2250	
Wheelbase	mm	1270				
Tread	Front	mm	778		767	
	Rear	mm	707-1035		743-1035	
Ground clearance	mm	250				270
Turning radius with brake	m	1.8				
Standard tyre	Front: Farm	4.5-10				5-12
	Rear: Farm	7-16				8-16
Weight	kg	460	510		520	
Comfort						
Headlamp	Multi-reflective		Multi-reflective with halogen valve (EC approved)			
Operator's deck			Semi-flat, full rubber covered deck			
Backlit instrument panel			STD			
Cup holder			STD			
Operator's noise level ^(*)	dB(A)	84			85	
Road approval ^(*)	Non-approved (CE marked model)		Approved (EC homologated model)			
Options						
EC approved rear-mounted ROPS kit			OPT			
EC approved back mirror kit	N/A		OPT			
Rear work-light kit			OPT			
EC approved drawbar kit	N/A		OPT (need for public road running)			
EC approved front hitch kit	N/A		OPT (need for public road running)			
Beacon lamp switch kit	N/A		OPT			
Hydraulic circuit changeover unit kit	OPT		STD			

The company reserves the right to change the above specifications without notice.

^(*) Manufacturer's estimates.

⁽²⁾ Mower deck can be attached to the tractor only with farm tyre 4.50-10, 7-16 and turf tyre 20x8.00-10, 212/80D-15.

⁽³⁾ For those who wish to use our tractors on public roads, please consider our road-approved B1620 and B1820 models.

©2009 Kubota Corporation



KUBOTA (U.K.) LIMITED

Dormer Road Thame, Oxfordshire, OX9 3UN.
Phone Thame (01844) 214500 Fax (01844) 216685
E-mail: sales@kubota.co.uk

Web site: <http://www.kubota.co.uk>