

TRACTOR SPECIFICATIONS

Model		B1220		B1620		B1820PS	
		w/o Mid-PTO		w/ Mid PTO		w/ Mid PTO	
Engine		E-TVCS, liquid cooled, 2-cylinder diesel		E-TVCS, liquid cooled, 3-cylinder diesel			
Type							
Make, Model		Kubota Z482		Kubota D722		Kubota D782	
Engine power SAE gross	kW (PS)	8.8 (12)		11.8 (16)		13.2 (18)	
Engine power ECE-R24	kW (PS)	7.9 (11)		10.3 (14)		11.9 (16)	
PTO power (*1)	kW (PS)	7.0 (9.5)		9.2 (12.5)		10.7 (14.5)	
No. of cylinders		2		3			
Bore & stroke	mm	67 × 68				67 × 73.6	
Total displacement	cm ³	479		719		778	
Rated speed	rpm	3100		2800			
Muffler and exhaust pipe				Fully enclosed			
Air cleaner				Single			
Fuel tank capacity	ℓ			14			
Drive train							
Driving method		4WD		2WD ⇄ 4WD			
Transmission speeds				F6/R2			
Max. travelling speed	km/h	15.1		17		18.1	
Differential lock				STD			
Brake type				Wet mulch disk			
Steering		Manual				Power steering	
PTO							
Rear PTO	Type			Transmission driven with one way clutch			
	Speed	rpm		540/1000			
Mid PTO (*2)	Speed	rpm		N/A		2500	
Hydraulic system							
Pump capacity	ℓ/min	8.2				14.1	
Lift control type				Select			
Lift capacity	Link end	kg		430		540	
Max. operating pressure	kg/cm ²	91				123	
3-point hitch				category I			
Hydraulic outlets		1 rear (OPT)				1 rear & 1 mid	
Hydraulic cylinder for mower lifting				N/A			
Dimensions							
Overall length	mm			2360			
Overall width (min. tread)	mm	932				940	
Overall height (Steering wheel / ROPS)	mm	1235 / N/A		1235 / 2230		1255 / 2250	
Wheelbase	mm			1270			
Tread	Front	mm		778		767	
	Rear	mm		707-1035		743-1035	
Ground clearance	mm	250				270	
Turning radius with brake	m			1.8			
Standard tyre	Front: Farm			4.5-10		5-12	
	Rear: Farm			7-16		8-16	
Weight	kg	460		510		520	
Comfort							
Headlamp		Multi-reflective		Multi-reflective with halogen valve (EC approved)			
Operator's deck				Semi-flat, full rubber covered deck			
Backlit instrument panel				STD			
Cup holder				STD			
Operator's noise level (*1)	dba	84		85			
Road approval (*3)		Non-approved (CE marked model)		Approved (EC homologated model)			
Options							
EC approved rear-mounted ROPS kit				OPT			
EC approved back mirror kit		N/A				OPT	
Rear work-light kit				OPT			
EC approved drawbar kit		N/A		OPT (need for public road running)			
EC approved front hitch kit		N/A		OPT (need for public road running)			
Beacon lamp switch kit		N/A		OPT			
Hydraulic circuit changeover unit kit		OPT		STD			

The company reserves the right to change the above specifications without notice.

(*1) Manufacturer's estimates.

(*2) Mower deck can be attached to the tractor only with farm tyre 4.50-10, 7-16 and turf tyre 20x8.00-10, 212/80D-15.

(*3) For those who wish to use our tractors on public roads, please consider our road-approved B1620 and B1820 models.

©2010 Kubota Corporation



KUBOTA (U.K.) LIMITED

Dormer Road Thame, Oxfordshire, OX9 3UN.
Phone Thame (01844) 214500 Fax (01844) 216685
E-mail: sales@kubota.co.uk

Web site: <http://www.kubota.co.uk>