

Specifications

Model		G23	G26
Engine			
Model		Kubota D902	Kubota D1005
Type		Water-cooled diesel (3 cyl.)	
Max. horsepower	HP	23.3	25.5
Total displacement	cc	988	1001
Air cleaner		Dual element	
Rated speed	rpm	3200	
Fuel tank capacity	ℓ	20.5	
Transmission		Hydrostatic transmission	
Type		Hydrostatic transmission	
Max. travel speed (Forward)	km/h	15.5	17.0
Differential lock		Standard	
Cruise control		Standard	
Speed control		F/R 1 pedal	
Type			
Front		16 x 7.5-8 turf	
Rear		24 x 12-12 turf	
Brake		Wet discs	
Steering		Hydrostatic power	
Type		Hydrostatic power	
Uncut radius	m	1.7	
Dimension			
Tread (F/R)	mm	925 / 840	
Wheel base	mm	1380	1450
Overall length	mm	2995	3236
Overall width	mm	1150	
Overall height (including G/C)	mm	1285 (top of seat)	1600 (G/C)
Weight (w/ mower and G/C) (HD / LD)	kg	840 / 690	890 / 735
Ground clearance (w/o mower)	mm	150	
Mower mounting		Gear drive	
Type		Gear drive	
PTO revolution		2614	
Clutch		Belt tension	Wet, hydraulic
Others			
Water temperature gauge		Standard	
Fuel gauge		Standard	
Hour meter / Tachometer		Standard	
Easy checker		Standard	
G/C			
Capacity	ℓ	560	640
Dumping height	mm	1930	
Sensor for G/C		Weight sensing	
Material of G/C bag (HD / LD)		Metal / Cloth	

Mower specifications

Model		GCK48-G23	CGK54-G26
Cutting width	inch (cm)	48 (122)	54 (137)
Mower drive method		Gear drive	
Mower lifting method		Hydraulic	
Mower lifting height	mm	150	
Cutting height	inch	1.0 – 4.0	
Cutting height adjustment		Dial (1/4")	
Number of blades		2	
Blades length	mm	673	748

The company reserves the right to change the specifications without notice. This brochure is for descriptive use only.

©2009 Kubota Corporation

Kubota

KUBOTA (U.K.) LIMITED

Dormer Road Thame, Oxfordshire, OX9 3UN.
Phone Thame (01844) 214500 Fax (01844) 216685
E-mail: sales@kubota.co.uk

Web site: <http://www.kubota.co.uk>