

# Specifications

Model		G23	G26
<b>Engine</b>			
Model		Kubota D902	Kubota D1005
Type		Water-cooled diesel (3 cyl.)	
Max. horsepower	HP	23.3	25.5
Total displacement	cc	898	1001
Rated speed	rpm	3200	
<b>Fuel tank capacity</b>	ℓ	20.5	
<b>Transmission</b>			
Type		Hydrostatic transmission	
Max. travel speed (Forward)	km/h	15.5	17.0
Differential lock		Standard	
Cruise control		Standard	
Speed control		F/R 1 pedal	
<b>Tyre</b>			
Front		16 x 7.5-8 turf	
Rear		24 x 12-12 turf	
<b>Brake</b>		Wet discs	
<b>Steering</b>			
Type		Hydrostatic power	
Uncut diameter	m	1.7	
<b>Dimension</b>			
Tread (F/R)	mm	900 / 840	
Wheel base	mm	1390	1460
Overall length (HD/LD w/o front weight bracket)	mm	3160 / 2980	3215 / 3035
Overall width	mm	1150	
Overall height (including G/C) (HD / LD)	mm	1600 / 1350 (steering)	
Weight (w/ mower and G/C) (HD / LD)	kg	840 / 690	890 / 735
Ground clearance (w/o mower)	mm	230	
<b>Mower mounting</b>			
Type		Gear drive	
PTO revolution		2600	
Clutch		Belt tension	Wet, hydraulic
<b>Others</b>			
Water temperature gauge		Standard	
Fuel gauge		Standard	
Hour meter / Tachometer		Standard	
Easy checker		Standard	

# Mower specifications

Model		RCK48-G23	RCK54-G26
Cutting width	inch (cm)	48 (122)	54 (137)
Mower drive method		Gear drive	
Mower lifting method		Hydraulic	
Mower lifting height	mm	150	
Cutting height	inch	1.0 - 4.0	
Cutting height adjustment		Dial (1/4")	
Number of blades		2	
Blades length	mm	673	748
<b>G/C</b>			
Capacity (HD / LD)	ℓ	640 / 560	
Dumping height	mm	1930	
Sensor for G/C		Weight sensing	
Material of G/C bag (HD / LD)		Metal / Cloth	

The company reserves the right to change the specifications without notice. This brochure is for descriptive use only.

©2009 Kubota Corporation



## KUBOTA (U.K.) LIMITED

Dormer Road Thame, Oxfordshire, OX9 3UN.  
 Phone Thame (01844) 214500 Fax (01844) 216685  
 E-mail: sales@kubota.co.uk

Web site: <http://www.kubota.co.uk>