

Specifications

Model		GZD15-LD	GZD15-HD
Engine	Model	Kubota Z602	
	Fuel type	Diesel Liquid-cooled (2 cyl.)	
	Displacement	599 cc (36.5 cu. in.)	
	Power	15 HP (11.2kw)	
	Fuel capacity	20 ℓ	
	Battery	12V (450 CCA)	
	Alternator	15 Amps	
Tractor	Mower position	Mid-Mount	
	Front axle pivot	Standard	
	Type	4Wheels-2WD	
	Tyre size Front/Rear	15×6.0-6 / 20.0×10-8	
	Tread Front	770 mm	
	Rear	950/850 mm 2 positions	
	Wheel base	1285 mm	
	Overall Length	2785 mm	
	Overall Width	1200 mm	
	Overall Height	1115 mm	1345 mm
	Weight (w/mower & GC)	510 kg	540 kg
Drive Train	Speed Front/Rear	0-13.5 km/h / 0-10 km/h	
	T/M drive system	Shaft drive	
	Mower drive system	Shaft drive	
	Drive system	2-HST	
	Steering style	2-Hand Levers	
	Parking brake	Wet multi-discs, Mechanical equalising brake system	
	Turning radius	0 m	
PTO	PTO clutch	Hydraulic Wet Multi Discs	
	PTO brake	Hydraulic Wet Single Disc	
Mower	Cutting width	42" (1067 mm)	
	Lift system	Hydraulic	
	Mount system	Parallel Linkage	
	Blade drive system	Hex belt, gear	
	Cutting height	1-4 in. (1/4"), 4-5 in. (1/2") (25-102 mm (6 mm), 102-127 mm (13 mm))	
	Cutting height adj.	Dial	
	Max. Mower lift height	135 mm	
	No. of blades	2	
Grass Collector	Type	Low dump/Hydraulic	High dump/Hydraulic
	Capacity	400 ℓ	
	Lift height (MAX)	1.8 m (5.9 ft)	

The company reserves the right to change the above specifications without notice.
This brochure is for descriptive purpose only. Please contact your local Kubota dealer for warranty information.

©2006 Kubota Corporation



KUBOTA (U.K.) LIMITED

Dormer Road Thame, Oxfordshire, OX9 3UN.
Phone Thame (01844) 214500 Fax (01844) 216685
Web site: <http://www.kubota.co.uk/>
E-mail: sales@kubota.co.uk