

Specifications

Model	RTV1140CPX	
Make	KUBOTA D1105-E3-JV	
Type	3-cylinders, Water cooled 4-cycle, diesel, OHV	
Displacement	cc	1123
Horsepower	HP (kW)/rpm	24.8 (18.5)@3000
Fuel tank capacity	ℓ	30
Transmission	Variable hydro transmission (VHT)	
Max. Traveling speed	km/h	40
Wheels, drive system	Rear 2WD or 4WD selection	
Differential lock	Standard; foot operated with mechanical holder	
Gear selection	Hi-Med-Lo range forward, neutral, reverse	
Front / Rear Parking brake	Wet-disc brake	
Brakes	Rear wheel, hand lever	
Steering	Hydrostatic power	
Suspension	Independent, Mac-Pherson strut-type / Semi-independent, DeDion axle w/leaf springs and shock absorbers	
Length	mm	3480
Width	mm	1550
Height, overall	mm	2000
Front tread centers	mm	1150
Rear tread centers	mm	1180
Wheelbase	mm	2415
Ground clearance front/rear axle	mm	190 / 190
Turning radius	m	5.0
Max. rolling weight (Towing capacity)	kg	590
Payload capacity	kg	740
Weight	kg	1075
Width x Length x Depth	1320x860x290 [2ROWS] / 1320x1360x290 [1ROW]	
Volume	m ³	0.33 [2ROWS] / 0.52 [1ROW]
Bed height (unloaded)	mm	820
Cargo bed load	kg	300 [2ROWS] / 500 [1ROW]
Tyres	Front	25x10-12 ATV, 6PLY
	Rear	25x11-12 ATV, 6PLY
Front guard	Std.	
Hydraulic bed lift	Std.	
Speedometer	Std.	

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty and safety information. The values in "Ground clearance" and "Weight" are those of the machine equipped with the tires in the table above. Some RTVs in this brochure are shown with optional accessories. For off-highway use only.

KUBOTA (U.K.) LIMITED

Dormer Road, Thame, Oxfordshire, OX9 3JN.
 Phone Thame (01844) 214500 Fax (01844) 216665
 E-mail: sales@kubota.co.uk

Web site: <http://www.kubota.co.uk>