

# SPECIFICATIONS

Model		RTV-X900
Available body colours		Orange / Camo
Engine	Make	KUBOTA D902
	Type	3-cylinders, 4-cycle, diesel, OHV
	Displacement ℓ	898
	Net Power ECE-R24 kW (PS)/rpm	15.4 (20.9)@3200
	Cooling system	Liquid
Battery		540 CCA
Transmission		Continuously Variable Hydro Transmission (VHT-X)
Gear selection		Hi-Lo range forward, neutral, reverse
Max. travelling speed km/h (mph)		0 – 40 (0 – 25)
4WD system	Front differential	Limited-slip differential
	Rear differential	Foot operated differential lock
Steering		Hydrostatic power
Brakes	Front / Rear	Wet-disc brakes
	Parking brake	Rear wheel, hand operated
Suspension	Front suspension	Independent, Dual A-arms with adjustable spring preload
	Rear suspension	Independent with coil over shock
Ground clearance	Front mm	266
	Rear mm	263
Dimensions	Length mm	3110
	Width mm	1605
	Overall height mm	2020
	Front tread centers mm	1240
	Rear tread centers mm	1240
	Wheelbase mm	2045
	Turning radius m	4.0
Weight kg		941
Towing capacity kg		1000
Payload capacity kg		679
Cargo bed	Structure	Steel
	Width × Length × Depth mm	1465 × 1030 × 285
	Volume m <sup>3</sup>	0.43
	Bed height (unloaded) mm	887
	Cargo bed load kg	500
	Dumping system	Hydraulic pump
Fuel tank capacity ℓ		30
Sound rating at operator's ear at max rpm dB. (A)		83.3
Tyres	ATV	25×10-12, 6-ply
	HDWS	25×10-12, 6-ply
Hydraulic bed lift		Standard
EC Homologated "Street Legal" Version		Available

The company reserves the right to change the above specifications without notice.

This brochure is for descriptive purpose only. Please contact your local Kubota dealer for warranty and safety information.

The values in "Ground clearance" and "Weight" are those with the machine equipped with the tyres in the table above. Some RTVs in this brochure are shown with optional accessories. For off-highway use only.