

## SPECIFICATIONS

<b>Model</b>	<b>GR1600-II</b>	
<b>Engine</b>		
Type	2 cylinder, diesel, water-cooled	
Gross horsepower	HP (kW)	13.5 (10)
Fuel tank capacity	ℓ	18
<b>Dimension</b>		
Overall length	mm	2710
Overall width	mm	1110
Overall height	mm	1190
<b>Transmission</b>	Hydrostatic transmission	
<b>Transmission drive</b>	Shaft drive	
<b>Travelling speed</b>		
Forward/Reverse	km/h	0–10.0/0–5.0
<b>PTO clutch</b>	Mechanical wet multi discs	
<b>Mower deck drive</b>	U-joint shaft	
<b>Operator's deck</b>	Flat	
<b>Seat adjustment</b>	Slide	
<b>Fuel gauge</b>	Std.	
<b>Easy checker®</b>	Std.	
<b>Mower OPC.</b>	Std.	
<b>Travel OPC.</b>	Std.	
<b>Blade shut off brake</b>	Built-in clutch	
<b>Mower shut off when collector open</b>	Std.	
<b>Grass collector</b>		
Capacity	ℓ	370
<b>Optional accessories &amp; implements</b>	Cruise control, rear deflector	

## MOWER SPECIFICATIONS

<b>Cutting width</b>	inch. (cm)	42 (107)
<b>Mower mounting method</b>	Quick attach	
<b>Cutting height</b>	mm	25–102
<b>Cutting height adjustment</b>	Dial	
<b>Cutting height position</b>	11	
<b>Minimum uncut diameter</b>	m	1.7

The company reserves the right to change the above specifications without notice. Some attachments shown may not be available in the UK.

©2006 Kubota Corporation



**KUBOTA (U.K.) LIMITED**

Dormer Road Thame, Oxfordshire, OX9 3UN.  
Phone Thame (01844) 214500 Telex 837551 Fax (01844) 216685