



KUBOTA WALK BEHIND MOWER

W821R-PRO / W821-PRO

From trimming well-kept lawns to mowing rough grass, a self-propelled Walk Behind Mower combining high durability with high performance — built for pros!



W821R-PRO
(ROLLER TYPE)

W821-PRO
(WHEEL TYPE)

FEATURES



BBC (Blade Brake Clutch)

The standard blade brake clutch stops the blade quickly for added safety. This allows emptying of the 75 L grass bag safely without stopping the engine.



Shaft Drive

The shaft drive rear wheel/roller transmission greatly reduces maintenance work compared to belt-driven mowers. Additionally, the shaft-mounted shock absorber also reduces slippage due to rain or grass clumps.



Heavy Duty Deck

The deck is a heavy duty aluminium die cast construction, reinforced with replaceable deckwear high durability parts.




Front Bumper

A front bumper comes standard to protect the deck from the impact of hitting trees or other obstacles.

Aluminium wheels

Stylish, wide-rimmed aluminium wheels and bearings come standard for added protection against corrosion. The large wheels provide increased manoeuvrability and traction while still maintaining durability for high-performance operation.



Discharge Chute

The large discharge chute design allows the machine to handle even high-moisture grass.

SPECIFICATIONS

| Model | W821-PRO | | W821R-PRO | |
|----------------------------|---|--|--------------------------------------|------------------------|
| Engine | | | | |
| Model | HONDA GXV160 | | | |
| Engine type | Air-cooled, 4-cycle OHV, Single-cylinder, petrol engine | | | |
| Fuel | Unleaded petrol for automobiles | | | |
| Displacement | 163 cm ³ | | | |
| Bore×Stroke | 68 mm × 45 mm | | | |
| Max. output | 3.2 kw / 3,600 rpm | | | |
| Max. torque | 9.6 Nm / 2,500 rpm | | | |
| Operation speed | 2,800 rpm | | | |
| Fuel tank capacity | 1.8 L | | | |
| Engine oil capacity | 0.65 L | | | |
| Ignition system | Transistorised magnet ignition | | | |
| Ignition plug | NGK : BPR 5 ES / DENSO : W 16 EPR-U | | | |
| Starting method | Recoil method | | | |
| Dimension | | | | |
| Outside dimensions (L×W×H) | 1,830 × 580 × 1,270 (mm) | | 1,810 × 580 × 1,260 (mm) | |
| Dry weight | 62 kg | | 58 kg | |
| Wheel diameter | 244 mm Aluminium wheel | | Front | 203 mm Aluminium wheel |
| | | | Rear | 102 mm Steel roller |
| Traveling Speed | 2-step gearshift | | Speed: 1.0 m/sec | |
| | Low speed: 1.0 m/sec | | | |
| | High speed: 1.4 m/sec | | | |
| Mower | | | | |
| Blade engagement | BBC (Blade Brake Clutch) | | | |
| Grass bag capacity | 75 L | | | |
| Cutting width | 530 mm | | | |
| Cutting height | 22,32,42,52,62,72,82 mm (7 Position) | | 15,26,37,47,57,67,77 mm (7 Position) | |

* The company reserves the right to change the above specifications without notice.



KUBOTA (U.K.) LIMITED

Domer Road Thame, Oxfordshire, OX9 3UN.
Phone Thame (01844) 268000 Fax(08702) 429677
E-mail: sales@kubota.co.uk

Web site: <http://www.kubota.co.uk>

Cat.No22160-01-UK Printed in Japan.Kubota eight corp. '13-Jan.